



UX10-EX FULLY RUGGED TABLET

- Certificazione ATEX/IECEx per zona potenzialmente esplosiva
- Processore Intel® Core™ di 10ª generazione
- Schermo LumiBond® 2.0 Full HD da 10,1 pollici con tecnologia Getac per la leggibilità alla luce diretta del sole (1.000 nit) e touchscreen capacitivo
- Maniglia rigida multi-funzione per la massima flessibilità sul lavoro
- Multiple opzioni configurabili per rispondere alle diverse situazioni di utilizzo



Maniglia rigida



Specifiche tecniche

Generation

G2

Operating System

Windows 10 Pro

Mobile Computing Platform

Intel® Core™ i5-10210U Processor 1.6GHz
Max. 4.2GHz with Intel® Turbo Boost Technology
- 6MB Intel® Smart Cache

Platform Options:

Intel® Core™ i5-10310U vPro™ Processor 1.7GHz
Max. 4.4GHz with Intel® Turbo Boost Technology
- 6MB Intel® Smart Cache

Intel® Core™ i7-10510U Processor 1.8GHz
Max. 4.9GHz with Intel® Turbo Boost Technology
- 8MB Intel® Smart Cache

Intel® Core™ i7-10610U vPro™ Processor 1.8GHz
Max. 4.9GHz with Intel® Turbo Boost Technology
- 8MB Intel® Smart Cache

VGA Controller

Intel® UHD Graphics

Display

10.1" IPS TFT LCD FHD (1920 x 1200)
Protection film
1000 nits LumiBond® display with Getac sunlight readable technology
Capacitive multi-touch screen

Storage & Memory

8GB DDR4
Optional: 16GB / 32GB DDR4
256GB PCIe NVMe SSD
Optional: 512GB / 1TB PCIe NVMe SSD

Keyboard

Power button
5 tablet programmable buttons

Pointing Device

Touchscreen
- Capacitive multi-touch screen
- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slot

Optional: 1D/2D imager barcode reader, or HF RFID readerⁱ, or LAN port (RJ45), or USB 3.2 Gen 1 Type-A, or USB 3.2 Gen 1 Type-C port, or VGA portⁱⁱ

I/O Interface

FHD webcam x 1^{viii}
8M pixels auto focus rear camera x 1
Headphone out / mic-in combo x 1
DC in Jack x 1
USB 3.2 Gen 2 Type-A x 1
HDMI x 1
Optional: Windows Hello face-authentication camera (front-facing) x 1^{viii}

Communication Interface

Intel® Wi-Fi 6 AX200, 802.11ax
Bluetooth (v5.1)^{ix}
Optional: dedicated GPS^v
Optional: 4G LTE mobile broadband with integrated GPS^v
Optional: 10/100/1000 base-T Ethernet

Security Feature

TPM 2.0
Kensington lock
Optional: Intel® vPro™ Technology
Optional: HF RFID readerⁱⁱ

Power

AC adapter (65W, 100-240VAC, 50 / 60Hz)
Li-Ion smart battery (11.1V, typical 4200mAh; min. 4080mAh)
Optional: High capacity battery (10.8V, 9240mAh) x 1

Dimension (W x D x H) & Weight

276.8 x 194.5 x 23.5 mm (10.89" x 7.65" x 0.92"),
1.24 kg (2.73 lbs)^x

Rugged Feature

MIL-STD-810H certified
IP65 certified
Vibration & 6 feet (180 cm) drop resistant^{vi, viii}
ATEX & IECEx certified

Environmental Specification

Temperature^{vii}:
- Operating: -21°C to 63°C / -6°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
Humidity:
- 95% RH, non-condensing

Explosion Protection

ATEX / IECEx Zone 2/22
Ex II 3G Ex ic op is IIC T4 Gc
Ex II 3D Ex ic op is IIB T1 30°C Dc

Pre-installed Software

Getac Utility
Getac Camera
Getac Geolocation
Getac Barcode Manager^x
Optional: Absolute Persistence[®]

Accessories

Battery (11.1V, typical 4200mAh; min. 4080mAh)
AC Adapter (65W, 100-240VAC)
Capacitive Stylus

Optional:

Battery (11.1V, typical 4200mAh; min. 4080mAh)
High Capacity Battery (10.8V, 9240 mAh)
Multi-bay charger (Dual Bay)
Multi-Bay charger (Eight-Bay)
AC adapter (65W, 100-240VAC)
Digitizer Pen
Capacitive stylus
Protection film
Hand strap
Shoulder strap (2-point)
Shoulder harness (4-point; handsfree)
100W Type-C Adaptor^x

Garanzia Bumper-to-Bumper

Gli imprevisti possono compromettere l'utilizzo dei dispositivi e causare tempi di inattività.

Ecco perché Getac ha introdotto la copertura dei danni accidentali come elemento standard della Garanzia totale Bumper-to-Bumper, consentendo una migliore gestione dei costi legati all'IT.

La Garanzia totale è una formula agevole che offre il servizio di logistica Pack & Collect e garantisce un servizio di assistenza e riparazione rapido, effettuato da personale qualificato di Getac e di una riconsegna altrettanto veloce.

In questo modo il dispositivo sarà nuovamente operativo nel giro di pochi giorni.

Standard

3 anni Garanzia totale Bumper-to-Bumper

- i 13.56MHz Contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- ii 1D/2D imager barcode reader, HF RFID reader, serial port, LAN port (RJ45), USB 3.2 Gen 1 Type-A, USB 3.2 Gen 1 Type-C port and VGA port are mutually exclusive options.
- iii Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- iv Supports GPS and Glonass.
- v Weight and dimensions vary from configurations and optional accessories.
- vi Drop test results vary from configurations and optional accessories.
- vii Tested by a national independent third party test lab following MIL-STD-810H.
- viii FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.
- ix Available when barcode reader option is selected.
- x Do not support the configurations with Discrete Graphic Card.

UX10-EX

Fully Rugged Tablet



Getac

GETAC TECHNOLOGY CORPORATION

Palazzo Cassiopea 3 - Centro Direzionale
Colleoni Via Paracelso 26
20864 - Agrate Brianza (MB)
Sales-getac-Italy@getac.com | www.getac.com/it/



Copyright © 2021 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Le informazioni riportate sono puramente indicative,
le specifiche disponibili sono da verificare al momento dell'offerta. V01M03Y21IT